

## **Section 1. Identification**

**Product name:** NYALIC® Clear Surface Protectant

**Product code:** HBI 400

**Other means of identification:** Not available.

**Product type:** Liquid

**Relevant identified uses of the substance or mixture and uses advised against:** Not applicable.

**Manufacturer:** HBI, INC.  
114 AIRPORT BUSINESS CT.  
JASPER, GA 30143  
[www.nyalic.com](http://www.nyalic.com)  
[info@nyalic.com](mailto:info@nyalic.com)

**Emergency telephone number of the company:** 706-253-1920

## **Section 2. Hazards Identification**

**OSHA/HCS status:** This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture:** *FLAMMABLE LIQUID* - Category 3  
*CHRONIC AQUATIC TOXICITY* – Category 1  
*SERIOUS EYE DAMAGE/ EYE IRRITATION* - Category 2A  
*CARCINOGENICITY* - Category 2  
*SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE)* - Category 4  
*SKIN IRRITATION* – Category 2  
*ASPIRATION HAZARD* - Category 1

**GHS label elements:**



**Classification according to Directive 67/548/EEC or Directive 1999/45/EC:**



Xi  
Irritant



N  
Dangerous  
for Environment



Xn  
Harmful

**Signal word:** DANGER

**Hazard statements:** H226 – Flammable liquid and vapor.  
H227 – Combustible liquid.  
H304 – May be fatal if swallowed and enters airways.  
H312 – Harmful in contact with skin.  
H315 – Causes skin irritation.  
H332 – Harmful if inhaled.  
H335 – May cause respiratory irritation.  
H336 – May cause drowsiness or dizziness.  
H351 – Suspected of causing cancer.  
H411 – Toxic to aquatic life with long lasting effects.

**Precautionary statements:**

**General:** Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

**Prevention:** P201 – Obtain special instructions before use.  
P202 – Do not handle until all safety precautions have been read and understood.  
P210 – Keep away from heat, sparks, open flames, hot surfaces – No Smoking.  
P233 – Keep container tightly closed.  
P241 – Use explosion proof electrical/ventilating/lighting equipment.  
P242 – Use only sparking tools.  
P243 – Take precautionary measures against static discharge.  
P261 – Avoid breathing dust, fumes, gas, mist, vapors.  
P264 – Wash hands thoroughly after handling.  
P271 – Use only outdoors or in a well-ventilated area.  
P273 – Avoid release to the environment.  
P280 – Wear protective gloves, protective clothing, eye and face protection.  
P281 – Use personal protective equipment (PPE) as required.

**Response:** P305 + P351 + P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P301 + P310 + P331 – IF SWALLOWED: DO NOT induce vomiting. Immediately call a POISON CENTER or a doctor/ physician.  
P303 + P361 + P353 – IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with plenty of soap and water. Shower.

P370 + P378 – In case of fire, use water spray, dry chemical, carbon dioxide or alcohol-resistant foam.  
P312 – Call a poison center/doctor if you feel unwell.  
P363 – Wash contaminated clothing before reuse.  
P332 + P313 – If skin irritation occurs, get medical advice/attention.  
P304 + P340 – IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

**Risk:** R36 + R37 + R39- Irritating to eyes, respiratory system and skin.  
R51 + R53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R65 – Damaging to lungs when swallowed.  
R66 – Repeated exposure may cause skin dryness or cracking.  
R67 – Vapors may cause drowsiness or dizziness.

**Safety:** S16 – Keep away from sources of ignition – No smoking.  
S23 – Do not breathe vapors.  
S24 + S25 – Avoid contact with skin and eyes.  
S36 + S37 + S39 – Wear suitable protective clothing, gloves, eye and face protection.  
S62 – If swallowed, do not induce vomiting. Seek medical advice immediately and show this label.

**Storage:** P403 + P235 – Store in a well-ventilated place. Keep cool.  
P405 – Store locked up.

**Disposal:** P501 – Dispose of contents/ container to an approved waste disposal plant. Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Potential Health Effects:** **Skin** – May cause irritation. May be harmful if absorbed through the skin. Could cause dermatitis upon prolonged contact.  
**Eyes** – May cause irritation, discomfort, pain and redness.  
**Inhalation** – Material is irritating to mucous membranes and upper respiratory tract. Harmful if inhaled. Inhalation of high concentrations may cause central nervous system effects characterized by headache, dizziness, nausea, vomiting, malaise, unconsciousness and coma. Vapors may cause dizziness or suffocation.  
**Ingestion** – May be harmful if swallowed. May cause irritation of the digestive tract. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May cause central nervous system depression characterized by excitement, followed by headache, dizziness, drowsiness and nausea. Advanced stages may cause collapse, unconsciousness, coma and possibly death due to respiratory failure. Aspiration of vomitus into the lungs must be avoided; DO NOT induce vomiting. Minute amounts aspirated into the lungs can produce severe lung injury, chemical pneumonitis, pulmonary edema or death.

**Supplemental label elements:**

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. Please refer to the SDS for additional information. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.

**Hazards not otherwise classified:**

None known.

### **Section 3. Composition/Information on Ingredients**

**Substance/mixture:** Proprietary Mixture

**Other means of identification:** Not available

**CAS number/other identifiers:**

<b><u>Ingredient name</u></b>	<b><u>CAS number</u></b>	<b><u>% Range</u></b>	<b><u>DSD</u></b>	<b><u>GHS/CLP</u></b>	<b><u>Reach Reg No.</u></b>
Solvent Naptha (petroleum)	64742-94-5 919-284-0	1 – 10	Xn N,R40,R65 R66,R6, R51/53	Danger, H304, H336,H351, H411& EUH066	01-2119463588-24
4-Chlorobenzotrifluoride	98-56-6	60 – 70	Xn, Xi, N		
2-Heptanone	110-43-0	1 – 10	Xn, Xi, N		
Acrylic resin	Trade secret	15 - 25			

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## **Section 4. First Aid Measures**

### **Description of necessary first aid measures:**

<b>Eye contact:</b>	Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Remove contact lenses after the first 2 minutes. Get medical attention immediately.
<b>Inhalation:</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
<b>Skin contact:</b>	Immediately flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated area with soap and water. If irritation persists, get medical attention. Wash and dry clothing before reuse. Clean shoes thoroughly before reuse.
<b>Ingestion:</b>	Get medical attention immediately. Call a poison center or physician. Never give anything to an unconscious or convulsive person. DO NOT induce vomiting. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### **Most important symptoms/effects, acute and delayed:**

<b>Eye contact:</b>	Causes eye irritation.
<b>Inhalation:</b>	Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
<b>Skin contact:</b>	No known significant effects or critical hazards.
<b>Ingestion:</b>	Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

**Over-exposure signs/symptoms:**

<b>Eye contact:</b>	Adverse symptoms may include the following - pain or irritation watering redness.
<b>Inhalation:</b>	Adverse symptoms may include the following - respiratory tract irritation, coughing, nausea or vomiting, headache drowsiness/fatigue dizziness/vertigo unconsciousness.
<b>Skin contact:</b>	No specific data.
<b>Ingestion:</b>	Adverse symptoms may include the following - nausea or vomiting.

**Indication of immediate medical attention and special treatment needed, if necessary:**

<b>Notes to physician:</b>	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
<b>Specific treatments:</b>	No specific treatment.
<b>First Aid Providers:</b>	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## **Section 5. Fire-fighting Measures**

**Extinguishing media:**

<b>Suitable extinguishing media:</b>	Use an extinguishing agent suitable for the surrounding fire. Water spray, carbon dioxide, foam, dry chemical, Halon, any "C" class.
<b>Unsuitable extinguishing media:</b>	None known.
<b>Hazardous thermal decomposition products:</b>	Decomposition products may include the following materials - carbon dioxide, carbon monoxide
<b>Special protective actions for fire-fighters:</b>	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
<b>Unusual Fire and Explosion Hazards:</b>	Vapors are heavier than air and may travel along the ground and could ignite from a distant source.

**Special protective equipment for fire-fighters:** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**Flash Point:** 102°F / 38.9°C

**Autoignition Temperature:** N/A

**Flammable Limits:** LEL: 1.2% UEL: 10.5%

## **Section 6. Accidental Release Measures**

### **Personal precautions, protective equipment and emergency procedures:**

**For non-emergency personnel:** No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders:** If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel."

**Environmental precautions:** Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### **Methods and materials for containment and cleaning up:**

**Small spill:** Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill:** Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Dispose of in accordance with U.S. Federal, State and local hazardous waste disposal regulations. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. U.S. regulations (CERCLA) requires reporting spills and releases to soil, water and air in excess of reportable quantities.

## **Section 7. Handling and Storage:**

### **Precautions for safe handling:**

<b>Protective measures:</b>	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid breathing vapors. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
<b>Advice on general occupational hygiene:</b>	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
<b>Conditions for safe storage, including any incompatibilities:</b>	Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

## **Section 8. Exposure Controls/Personal Protection**

<b>Appropriate engineering controls:</b>	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
<b>Environmental exposure:</b>	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **Individual protection measures:**

<b>Hygiene measures:</b>	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
--------------------------	---



**Eye/face protection:** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

**Skin protection:**

**Hand protection:** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

**Other skin protection:** Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection:** Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

<b>CAS #</b>	<b>Partial Chemical Name</b>	<b>OSHA TWA</b>	<b>ACGIH TWA</b>
98-56-6	4-Chlorobenzotrifluoride	N/E	N/E
Proprietary	Acrylic resin	N/A	N/A
64742-94-5	Solvent naphtha (petroleum), (Heavy aromatic)	PEL: 500 ppm	N/E
110-43-0	2-Heptanone	PEL: 100 ppm	TLV: 50 ppm

## **Section 9. Physical and Chemical Properties**

### **Appearance:**

Physical state:	Liquid
Color:	No color; clear
Odor:	Aromatic
Odor threshold:	Characteristic hydrocarbon
pH:	Not available
Boiling point:	Greater than 300°F / 148.9°C
Flash point:	102°F / 38.9°C
Explosive limits:	LEL:1.0            UEL: 7.0
Evaporation rate:	Slower than ether
Flammability (solid, gas):	Not available
Lower and upper explosive (flammable) limits:	LEL: 1.2% Upper: 10.5%
Vapor pressure:	8.4 @ 68°F
Vapor density:	>1 [Air = 1]
Specific Gravity (H <sub>2</sub> O = 1):	0.85
Solubility:	Negligible
Auto-ignition temperature:	Above 1200°F (648.9°C)
Decomposition temperature:	N/A
Viscosity:	Like that of water
Weight per gallon:	10.1 ± 0.25
VOC's:	3.34 lbs/gal – 400 g/L
VOC's as applied:	0.278 lbs/gal / 100 ft <sup>2</sup> @ 1200 ft <sup>2</sup> /gal

## **Section 10. Stability and Reactivity**

<b>Reactivity:</b>	No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability:</b>	The product is stable under normal use conditions.
<b>Possibility of hazardous reactions:</b>	Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid:</b>	Avoid all possible sources of ignition (spark or flame). Prevent vapor accumulation.
<b>Incompatible materials:</b>	Strong oxidizers, bases.
<b>Hazardous decomposition products:</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced. In case of fire, oxides of carbon, hydrocarbons, fumes or vapors, smoke or various organic compounds may be produced.

## **Section 11. Toxicological Information**

### **Information on toxicological effects:**

#### **Acute toxicity:**

Epidemiology.	No information found.
Teratogenicity:	No information found.
Reproductive Effects:	No information found.
Mutagenicity:	No information found.
Neurotoxicity.	No information available.

Irritation or Corrosion: Serious eye damage/eye irritation.

Carcinogenicity/Other Information: Carcinogenicity  
IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.  
ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.  
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.  
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. This product contains the following substances known to the State of California to cause cancer, birth defects, or other reproductive hazards: Benzene, Toluene

## **Section 12. Ecological Information**

**Aquatic Toxicity:** No data available.











**Bioaccumulative potential:** No data available.

**Mobility in soil:** No data available.

## Section 13. Disposal Considerations

**Disposal methods:** Dispose of as unused product. The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any Federal, State and regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## Section 14. Transport Information

	<b>DOT Classification</b>	<b>TDG Classification</b>	<b>Mexico Classification</b>	<b>IATA/ ICAO</b>	<b>IMDG</b>
<b>UN Number</b>	NA 1993	UN 1993	UN 1993	UN 1993	UN 1993
<b>UN Proper Shipping Name</b>	Flammable liquid, n.o.s (Nyalic - CAL)	Flammable liquid, n.o.s (Nyalic - CAL)	Flammable liquid, n.o.s (Nyalic - CAL)	Flammable liquid, n.o.s (Nyalic - CAL)	Flammable liquid, n.o.s (Nyalic - CAL)
<b>Transport Hazard Class</b>	3	3	3	3	3
					
			OR		
					
<b>Packing Group</b>	III	III	III	III	III
<b>Environmental Hazards</b>	No	No	No	No	No
<b>Additional Information</b>	<u>Special Provisions</u> Limited Quantity	<u>Special Provisions</u> Limited Quantity	<u>Special Provisions</u> Limited Quantity	<u>Special Provisions</u> Limited Quantity	<u>Special Provisions</u> Limited Quantity

**Special Precautions for User:** Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

**Transport in bulk according to:** Not available.  
**Annex II of MARPOL**  
**73/78 and the IBC Code**

## **Section 15. Regulatory Information**

**U.S. Federal Regulations:** SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

### **EPA SARA (Superfund Amendments and Reauthorization Act of 1986) LISTS:**

<b>Hazardous Component</b>	<b>CAS number</b>	<b>S. 302 (EHS)</b>	<b>S. 304 RQ</b>	<b>S.313 (TRI)</b>
Solvent Naptha (petroleum) Heavy aromatic	64742-94-5	No	No	No
4-Chlorobenzotrifluoride	98-56-5	No	No	No
2-Heptanone	110-43-0	No	No	No
Acrylic resin	Trade secret	No	No	No

**State Regulations:** California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**CERCLA:** Not applicable.

**TSCA:** The components of this product are listed on the TSCA Inventory or are exempted from the list.

## **Section 16. Other Information**

### **Hazardous Material Information System III (U.S.A.)**

HEALTH	2
FLAMMABLE	2
REACTIVITY	0
PHYSICAL	0

**Caution:** HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS ratings are not required on SDS's under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS ratings are to be used with a fully implemented HMIS program. HMIS is a registered mark of the National Paint & Coatings Association (NPCA). HMIS materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

**Latest Revision:** August 1, 2020

The information contained herein is given to the receiver in good faith to the best of our knowledge. Nothing contained herein grants or extends a license, expressed or implied, in connection with patents, issued or pending, or the manufacturer or others. The information contained herein is based on the manufacturer's own gathering and the works of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. The manufacturer shall not be held liable (regardless of fault) to the receivers, employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information.